



# RESCUE RESCUE SAWS & BLADES – IN STOCK TODAY!



As of 2020, SHARK 20" Ventilation Chainsaws come in two sizes, 64 drive links and 66 drive links. We offer this choice to assist integrating SHARK saws into your fleet as replacements for discontinued brand models. If you count the drive links on your existing chainsaw, you can order our SHARK Ventilation Chainsaw with the same number of drive links. This will help ease management of spare chains in your fleet. Please count your drive links so you can order the correct model.

**NOTE:** As of 2020, all SHARK 20" Ventilation Chainsaws come with 66 drive links standard unless you request otherwise.

## TEAM SHARK VENTILATION CHAINSAWS SPECIFICATIONS



MODEL	SHARK II - 16" - 54DL	SHARK II - 20" 64DL	SHARK II - 20" 66DL	SHARK III - 16" - 54DL	SHARK III - 16" - 64DL	SHARK III - 16" - 66DL
PART NO.	TS2-57216	TS2-5722064	TS2-5722066	TS3-39016	TS3-3902064	TS3-3902066

POWER	MANUFACTURER					
	HUSQVARNA®					
	POWER HEAD	572 XP	572 XP	572 XP	390 XP	390 XP
	POWER OUTPUT	5.8hp / 4.3kw	5.8hp / 4.3kw	5.8hp / 4.3kw	6.5hp / 4.8kw	6.5hp / 4.8kw
DISPLACEMENT	4.3ci / 70.6cc	4.3ci / 70.6cc	4.3ci / 70.6cc	5.37ci / 88cc	5.37ci / 88cc	5.37ci / 88cc

CHAIN	DRIVE LINKS	54 DRIVE LINKS	64 DRIVE LINKS	66 DRIVE LINKS	54 DRIVE LINKS	64 DRIVE LINKS	66 DRIVE LINKS
	TYPE	HIGH IMPACT CARBIDE TIPPED CHAIN					
	CUTTER TYPE	CARBIDE FLAT 25° - DUAL RAKER					
	PITCH	0.404 inch					
	GAUGE	0.063 inch					

BAR	TYPE										
	HARDENED STEEL										
	DEPTH GAUGE READY										
	YES - SLOTTED FOR CDA-80 DEPTH GAUGE										
	NOSE TYPE										
	SPROCKET WITH SEALED BEARING										
DURABILITY											
HARDENED STEEL - REVERSABLE FOR EXTENDED LIFE											
GAUGE											
0.063 inch											
LENGTH (NOT MOUNTED)											
18-1/2"		22-3/8"		23"		18-1/2"		22-3/8"		23"	

DEPTH GAUGE	INCLUDED										
	YES										
	TYPE										
	CDA-80										
	ATTACHMENT TYPE										
OPEN – SLOT MOUNTED – EASY ONE HAND ON/OFF											
MATERIAL											
ALUMINUM											
DEPTH ADJUSTMENT											
2" to 9" Apx.		2" to 10" Apx.		2" to 9" Apx.		2" to 9" Apx.		2" to 10" Apx.		2" to 9" Apx.	

DIMENSIONS	WEIGHT	20.2 lbs / 9.2 kg	20.9 lbs / 9.5 kg	21.1 lbs / 10.9 kg	22.2 lbs / 10.1 kg	22.9 lbs / 10.4 kg	23 lbs / 10.4 kg	
	LENGTH	32.5 in / 826 mm	36.5 in / 927 mm	37.5 in / 953 mm	32.5 in / 826 mm	36.5 in / 927 mm	37.5 in / 953 mm	37.5 in / 953 mm
	WIDTH	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm
	HEIGHT	12.5 in / 318 mm	12.5 in / 318 mm	12.5 in / 318 mm	13.2 in / 335 mm	13.2 in / 335 mm	13.2 in / 335 mm	13.2 in / 335 mm

OTHER	FULL WRAP HANDLE					
	YES					
	SCRENCH TOOL HOLDER					
	YES					
	"D" STARTER HANDLE					
	YES					
	X-TORQ POWER					
	YES					
	AUTOTUNE CARB.					
	YES			NO		
	SPARK PLUG					
CHAMPION RCJ7Y / NGK BPMR7A						
FUEL CAPACITY						
0.185 gal / 0.70 L			0.238 gal / 0.90 L			
FUEL TYPE						
87 OCTANE GASOLINE OR HIGHER - 2 STROKE OIL MIXED 50:1						
BAR OIL CAPACITY						
0.425 qt / 0.40 L			0.53 qt / 0.50 L			
NOISE LEVEL						
AT OPERATOR 105 db			AT OPERATOR 107 db			
WARRANTY						
1 YEAR						